


Intersection Name: 82nd Avenue @ Glisan
Controller 2113.2 Channel: 212 Drop: 18
System: TransCore TransSuite TCS
Controller Type: Voyage
Revision - Version -
TransCore Unified Controller Manager 8.1.0



Zero Tables

- DetectorPlans
- DetectorFailMonitor
- Vehicle Overlaps
- PedOverlaps
- ADVANCE WARNING
- DynamicPhaseLength
- PlatoonProgression
- ForceOffPercents
- DayProgram 41 80
- DayProgram 81 120
- DayProgram 121 160
- DayProgram 161 200
- ExceptionDays
- PreemptionSequence 5 8
- PriorityReturnAndSpecialIntervals
- LightRailTrain
- TruckPriority
- CommandBox 1 96
- CommandBox 97 192
- CommandBox 193 256

Non-Zero Tables

- ControllerFunctionTiming
- Phase Timing
- Dual Entry
- OtherControllerFunctions
- DetectorData
- SystemDetector
- FYLTA
- ServicePlans1 4
- ServicePlans5 8
- MaxPlans
- CoordinationModes
- CoordinationPlans
- CoordinationPlansCont
- CircuitMapping
- DayProgram 1 40
- WeekProgram
- YearDays
- TimeClockReferences
- CircuitOverrides 1 98
- CircuitOverrides 99 198
- PreemptionSequence 1 4
- SequenceTiming
- CommData
- CommReports
- TransitPriority
- TransitPriorityAOF
- GroupTiming
- IO Options
- 170 Inputs
- 170 Outputs
- CONTROLLER ID

Controller Function and Timing

Security, Sequence and Timing (Next/2/1, Next/2/2/3/A, Next/2/2/5)					
Security Code	0	0 = disabled, or 1000-9999	First All Red	8.0	0.0 to 25.5 seconds
Sequence	7	0 = sequential, 1 = quad left turn, 2-6 = special A-E, 7 = lead lag			
Power up Flash	0.0				

Initialization (Next/2/2/5)			Lead Lag (Next/2/2/3/A)			
Ring 1	Ring 2	Interval	Phases 1 - 2	Phases 3 - 4	Phases 7 - 6	Phases 7 - 8
2	6	2	2	2	2	2
Phase 1 - 8		0 = Red, 1 = Yel, 2 = Grn	0 = no reversal, 1 = reversal, 2 = by coord plan or clock			

Phase Functions (Next/2/2/3, Next/2/2/1)								
Phase Used	1	2	3	4	5	6	7	8
Restricted Phases	-	-	-	-	-	-	-	-
Exclusive Phases	-	-	-	-	-	-	-	-
Yellow Lock	-	-	-	-	-	-	-	-
Min Recall	-	2	-	4	-	6	-	8
Max Recall	-	2	-	4	-	6	-	8
Ped Recall	-	2	-	4	-	6	-	8
Red Lock	-	-	-	-	-	-	-	-
Max Out Recall Inhibit	-	-	-	-	-	-	-	-
Soft Recall	-	-	-	-	-	-	-	-
Free Walk Rest	-	-	-	-	-	-	-	-
Conditional Ped	-	-	-	-	-	-	-	-
Disable Inhibit Max	-	-	-	-	-	-	-	-

Phase Times (Next/2/2/2, Next/2/2/9/5)									
Movement	1	2	3	4	5	6	7	8	
Movement									
Minimum Green	3	10	3	10	5	10	3	10	0 - 255 sec.
Passage	1.0	0.0	1.0	0.0	2.0	0.0	1.0	0.0	0.0 - 25.5 sec.
Yellow	3.0	3.6	3.0	3.6	3.0	3.6	3.0	3.6	0.0 - 25.5 sec.
Red Clearance	0.0	1.0	0.0	1.0	0.0	1.0	0.0	1.0	0.0 - 25.5 sec. or 0 - 255 sec.
Max 1	18	50	15	34	23	50	15	34	0 - 255 sec.
Max 2	18	50	15	27	17	50	15	27	0 - 255 sec.
Walk	0	9	0	8	0	10	0	8	0 - 255 sec.
Ped Clear	0	11	0	13	0	11	0	13	0 - 255 sec.
Seconds Per Actuation	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0 - 25.5 sec.
Time Before Reduction	0	0	0	0	8	0	0	0	0 - 255 sec.
Time to Reduce	0	0	0	0	15	0	0	0	0 - 255 sec.
Minimum Gap	1.0	0.0	1.0	0.0	1.0	0.0	1.0	0.0	0.0 - 25.5 sec.
Max Variable Initial	3	10	3	10	8	10	3	10	0 - 255 sec.
Max Extend	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0 - 25.5 sec.
Auto Max	0	0	0	0	0	0	0	0	0 - 255 sec.
Inhibit Min Yellow									X = On
Red Decimal Off									X = On

Dual Entry (Next/2/2/9/3)

Mode	1	0 = off, 1 = on, 2 = Not Used, 3 = by coord plan, 4 = by time clock
------	---	---

Dual Entry Ph -->	1	2	3	4	5	6	7	8	
Phase	0	6	0	8	0	2	0	4	0 = none, 1-8 = phase 1-

Cond Service (Next/2/2/7/3,			5 Sec Head Logic (Next/2/2/9/4)						
	Mode	CS Max Time	X Omits Y		Anti-Trap			Yellow Blanking	
Phase 1	0	0	X:Y		Trap Protected		Next	Phase	
Phase 3	0	0	6:1	0	1	0	< (5)	1	0
Phase 5	0	0	8:3	0	3	0	< (7)	3	0
Phase 7	0	0	2:5	0	5	0	< (1)	5	0
0 = off, 1 = C.S.On. 2 = C.S. on by TOD circuit 57, 3 = N/A, 4 = C.S. and C.R. On, 5 = C.R. on by TOD circuit 57.			4:7	0	7	0	< (3)	7	0
			0 = off, 1 = side call, 2 = no side call		X = On				

Other Controller Functions (Next/2/2/9/1, Next/2/2/9/5)

Inhibit Simultaneous Gap Out	- - - - -	
Last Car Passage	2	0 = recall phase, 1 = last car passage, 2 = NOT recall - Not last car passage
Red Revert (+2seconds)	0.0	0 - 25.5 sec.
Auto Ped Clear	Off	X = On
FDW thru Yellow	Off	X = On
Soft Recall Delay	0.0	0 - 25.5 sec.
Change Sequence	Off	X = On (After a download without a power on - off cycle)

Phase ->	1	2	3	4	5	6	7	8	
Red Clear Extension Detector	0	0	0	0	0	0	0	0	0 = none 1 - 32 = detector 1 -
Red Clear Extension Red Time	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0 - 25.5 sec.

Local Detectors (Next/2/2/4/1)

Detector Data

Detector	Description	Yellow Lock	Detector Inhibit	Call Phase	Extend Phase	Switch Phase	Delay Time	Stretch / Disconnect Time	Delay or Disconnect Mode
1				1	1	0	0	0.0	0
2				1	1	0	0	0.0	0
3				3	3	0	0	0.0	0
4				3	3	0	0	0.0	0
5				5	5	0	0	0.0	0
6				5	5	0	0	0.0	0
7				7	7	0	0	0.0	0
8				7	7	0	0	0.0	0
9				2	2	0	0	0.0	0
10				2	2	0	0	0.0	0
11				2	2	0	0	0.0	0
12				2	2	0	0	0.0	0
13				2	2	0	0	0.0	0
14				4	4	0	0	0.0	0
15				4	4	0	0	0.0	0
16				4	4	0	0	0.0	0
17				4	4	0	0	0.0	0
18				4	4	0	0	0.0	0
19				6	6	0	0	0.0	0
20				6	6	0	0	0.0	0
21				6	6	0	0	0.0	0
22				6	6	0	0	0.0	0
23				6	6	0	0	0.0	0
24				8	8	0	0	0.0	0
25				8	8	0	0	0.0	0
26				8	8	0	0	0.0	0
27				8	8	0	0	0.0	0
28				8	8	0	0	0.0	0
29				0	0	0	0	0.0	0
30				0	0	0	0	0.0	0
31				0	0	0	0	0.0	0
32				0	0	0	0	0.0	0

yellow lock, detector inhibit, - X = On; call, extend, phase - 0 = none 1 - 8 = phase 1 - 8; delay time - 0 - 255 sec
stretch / disconnect time - 0.0 - 25.5 sec.; delay or disconnect Mode - 0 -12

Detector Plans (Next/2/2/4/5)

Loop Number										
Plan Detectors		0	0	0	0	0	0	0	0	0 - 32, 0 = none, 1 - 32 = detectors 1 - 32
Detector Plan 2	Call Phase	0	0	0	0	0	0	0	0	0 - 8, 0 = none, 1 - 8 = phase 1 - 8
	Extended Phase	0	0	0	0	0	0	0	0	
	Switch Phase	0	0	0	0	0	0	0	0	
	Delay Time	0	0	0	0	0	0	0	0	
	Stretch / Disconnect Time	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	
	Delay / Disconnect Mode	0	0	0	0	0	0	0	0	
Detector Plan 3	Call Phase	0	0	0	0	0	0	0	0	0 - 8, 0 = none, 1 - 8 = phase 1 - 8
	Extended Phase	0	0	0	0	0	0	0	0	
	Switch Phase	0	0	0	0	0	0	0	0	
	Delay Time	0	0	0	0	0	0	0	0	
	Stretch / Disconnect Time	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	
	Delay / Disconnect Mode	0	0	0	0	0	0	0	0	
Detector Plan 4	Call Phase	0	0	0	0	0	0	0	0	0 - 8, 0 = none, 1 - 8 = phase 1 - 8
	Extended Phase	0	0	0	0	0	0	0	0	
	Switch Phase	0	0	0	0	0	0	0	0	
	Delay Time	0	0	0	0	0	0	0	0	
	Stretch / Disconnect Time	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	
	Delay / Disconnect Mode	0	0	0	0	0	0	0	0	

Detector Fail (Next/2/2/4/3)

Detector Fail Sample Period (all detectors)		0	0 - 255 minutes						
Video Fail Inputs	1	2	3	4	5	6	7	8	0 = none, 1 - 8 = phase 1 - 8
Phase Recalled	0	0	0	0	0	0	0	0	
System Detectors	1	2	3	4	5	6	7	8	0 = none, 1 - 32 = detector 1 - 32
Local Detector	0	0	0	0	0	0	0	0	

Flash (Next/2/2/5)

Flash Entry			Flash Exit		
Ring 1	Ring 2	Interval	Ring 1	Ring 2	Interval
2	6	red	2	6	2
0 = none, phase 1 - 8			0 = none, phase 1 - 8		0 = red, 1 = yel, 2 = grn

Soft Flash (Next/2/2/5)

Phase	1	2	3	4	5	6	7	8				
	3	4	3	4	3	4	3	4				
Overlap	A	B	C	D	E	F	G	H	I	J	K	L
	3	4	3	4	3	4	3	4	3	4	3	4
0 = dark, 1=flash yel WIG, 2 = flash yel WAG, 3 = flash red WIG, 4 = flash red WAG												

Internal Logic Output	1	2	3	4	5	6	7	8	9	10	11	12	0 = normal, 1 = dark, 2 = flash WIG
	0	0	0	0	0	0	0	0	0	0	0	0	

Overlaps / FYLTA (Next/2/2/8/1)

Vehicle Overlaps	Phase or Movement	Phase or Movement								Extension Green	Clearance		A - D 0 = no overlap 1 = overlap 2 = 60 FPM 3 = Not ped ov 4 = Comp Pha 5 = Prevent Ex 6 = Not Vehicle
		1	2	3	4	5	6	7	8		Yellow	Red	
A		0	0	0	0	0	0	0	0	0.0	0.0	0.0	E - L 0 = no Overlap 1 = Overlap Green, Yellow, 0.0 - 25.5 sec
B		0	0	0	0	0	0	0	0	0.0	0.0	0.0	
C		0	0	0	0	0	0	0	0	0.0	0.0	0.0	
D		0	0	0	0	0	0	0	0	0.0	0.0	0.0	
E		0	0	0	0	0	0	0	0	0.0	0.0	0.0	
F		0	0	0	0	0	0	0	0	0.0	0.0	0.0	
G		0	0	0	0	0	0	0	0	0.0	0.0	0.0	
H		0	0	0	0	0	0	0	0	0.0	0.0	0.0	
I		0	0	0	0	0	0	0	0	0.0	0.0	0.0	
J		0	0	0	0	0	0	0	0	0.0	0.0	0.0	
K		0	0	0	0	0	0	0	0	0.0	0.0	0.0	
L		0	0	0	0	0	0	0	0	0.0	0.0	0.0	

(Next/2/2/8/6/8)		Ped Overlaps (Next/2/2/8/5)					
Overlap	Not Ped-Ped Overlaps	Ped Overlap	Phase	Walk	Ped Clear	Walk, Ped Clear 0 - 255 seconds	
A	- - - - -	A	- - - - -	0	0		
B	- - - - -	B	- - - - -	0	0		
C	- - - - -	C	- - - - -	0	0		
D	- - - - -	D	- - - - -	0	0		
		E	- - - - -	0	0		
		F	- - - - -	0	0		
		G	- - - - -	0	0		
		H	- - - - -	0	0		

Flashing Yellow Left Turn Arrow (FYTLA) (Next/2/2/8/6)					
Phase Pairs ->	1 - 2	3 - 4	5 - 6	7 - 8	
Enable	0	0	0	0	0 = off, 3 = 3 outputs, 4 = 4 outputs, 5 = 5
Even Omits Odd	0	0	0	0	X = on, odd phase must be omitted
Detector Switch Odd /	0	0	0	0	X = on, odd phase must be omitted
Red Transition	2.0	2.0	2.0	2.0	0.0 or 2.0 - 25.5 sec.
Red Extension	0.0	0.0	0.0	0.0	0.0 - 25.5 sec.
Return to GLTA	0	0	0	0	0 = off, 1 = max out, 2 = yellow lock

Advance Warning (Next/2/2/8/3)									
	E	F	G	H	I	J	K	L	
Enable	0	0	0	0	0	0	0	0	0 = Disable, 1 = Enable
1st Conditional Overlaps	0	0	0	0	0	0	0	0	0 = None, 1 = OL E, 2 = OL F, 3 = OL G, 4 =
2nd Conditional Overlaps	0	0	0	0	0	0	0	0	OL H, 5 = OL I, 6 = OL J, 7 = OL K, 8 = OL L
Advance Deactivation Delay	0	0	0	0	0	0	0	0	0 - 99 sec

Service Plans 1 - 4 (Next/2/2/6)

	Phase ->	1	2	3	4	5	6	7	8	
Service Plan 1	Call Mode	4	0	0	0	0	0	0	0	
	0 = actuated, 1 = omit, 2 = N/A, 3 = min recall, 4 = max recall, 5 = soft recall, 6 = ped recall, 7 = omit ped, 8 = red rest									
	Min Green	3	10	3	10	3	10	3	10	0 - 255 sec
	Passage	1.0	0.0	1.0	0.0	1.0	0.0	1.0	0.0	0.0 - 25.5 sec.
	Yellow	3.0	3.6	3.0	3.6	3.0	3.6	3.0	3.6	0.0 - 25.5 sec. or 3.0 - 25.5
	Red	0.0	1.0	0.0	1.0	0.0	1.0	0.0	1.0	0.0 - 25.5 sec.
	Walk	0	9	0	8	0	10	0	8	0 - 255 sec
	Ped Clearance	0	11	0	13	0	11	0	13	0 - 255 sec

Service Plan 2	Call Mode	4	0	0	0	0	0	0	0	
	0 = actuated, 1 = omit, 2 = N/A, 3 = min recall, 4 = max recall, 5 = soft recall, 6 = ped recall, 7 = omit ped, 8 = red rest									
	Min Green	3	10	3	10	3	10	3	10	0 - 255 sec
	Passage	1.0	0.0	1.0	0.0	1.0	0.0	1.0	0.0	0.0 - 25.5 sec.
	Yellow	3.0	3.6	3.0	3.6	3.0	3.6	3.0	3.6	0.0 - 25.5 sec. or 3.0 - 25.5
	Red	0.0	1.0	0.0	1.0	0.0	1.0	0.0	1.0	0.0 - 25.5 sec.
	Walk	0	9	0	5	0	10	0	5	0 - 255 sec
	Ped Clearance	0	11	0	13	0	11	0	13	0 - 255 sec

Service Plan 3	Call Mode	0	0	0	0	0	0	0	0	
	0 = actuated, 1 = omit, 2 = N/A, 3 = min recall, 4 = max recall, 5 = soft recall, 6 = ped recall, 7 = omit ped, 8 = red rest									
	Min Green	3	10	3	10	3	10	3	10	0 - 255 sec
	Passage	1.0	0.0	1.0	0.0	1.0	0.0	1.0	0.0	0.0 - 25.5 sec.
	Yellow	3.0	3.6	3.0	3.6	3.0	3.6	3.0	3.6	0.0 - 25.5 sec. or 3.0 - 25.5
	Red	0.0	1.0	0.0	1.0	0.0	1.0	0.0	1.0	0.0 - 25.5 sec.
	Walk	0	9	0	8	0	10	0	8	0 - 255 sec
	Ped Clearance	0	11	0	13	0	11	0	13	0 - 255 sec

Service Plan 4	Call Mode	0	0	0	0	0	0	0	0	
	0 = actuated, 1 = omit, 2 = N/A, 3 = min recall, 4 = max recall, 5 = soft recall, 6 = ped recall, 7 = omit ped, 8 = red rest									
	Min Green	3	10	3	10	3	10	3	10	0 - 255 sec
	Passage	1.0	0.0	1.0	0.0	1.0	0.0	1.0	0.0	0.0 - 25.5 sec.
	Yellow	3.0	3.6	3.0	3.6	3.0	3.6	3.0	3.6	0.0 - 25.5 sec. or 3.0 - 25.5
	Red	0.0	1.0	0.0	1.0	0.0	1.0	0.0	1.0	0.0 - 25.5 sec.
	Walk	0	9	0	8	0	10	0	8	0 - 255 sec
	Ped Clearance	0	11	0	13	0	11	0	13	0 - 255 sec

Service Plans 5 - 8 (Next/2/2/6)

	Phase ->	1	2	3	4	5	6	7	8	
Service Plan 5	Call Mode	0	0	0	0	0	0	0	0	
	0 = actuated, 1 = omit, 2 = N/A, 3 = min recall, 4 = max recall, 5 = soft recall, 6 = ped recall, 7 = omit ped, 8 = red rest									
	Min Green	3	10	3	10	3	10	3	10	0 - 255 sec
	Passage	1.0	0.0	1.0	0.0	1.0	0.0	1.0	0.0	0.0 - 25.5 sec.
	Yellow	3.0	3.6	3.0	3.6	3.0	3.6	3.0	3.6	0.0 - 25.5 sec. or 3.0 - 25.5
	Red	0.0	1.0	0.0	1.0	0.0	1.0	0.0	1.0	0.0 - 25.5 sec.
	Walk	0	9	0	8	0	10	0	8	0 - 255 sec
	Ped Clearance	0	11	0	13	0	11	0	13	0 - 255 sec

Service Plan 6	Call Mode	0	0	0	0	0	0	0	0	
	0 = actuated, 1 = omit, 2 = N/A, 3 = min recall, 4 = max recall, 5 = soft recall, 6 = ped recall, 7 = omit ped, 8 = red rest									
	Min Green	3	10	3	10	3	10	3	10	0 - 255 sec
	Passage	1.0	0.0	1.0	0.0	1.0	0.0	1.0	0.0	0.0 - 25.5 sec.
	Yellow	3.0	3.6	3.0	3.6	3.0	3.6	3.0	3.6	0.0 - 25.5 sec. or 3.0 - 25.5
	Red	0.0	1.0	0.0	1.0	0.0	1.0	0.0	1.0	0.0 - 25.5 sec.
	Walk	0	9	0	8	0	10	0	8	0 - 255 sec
	Ped Clearance	0	11	0	13	0	11	0	13	0 - 255 sec

Service Plan 7	Call Mode	0	6	0	6	0	6	0	0	
	0 = actuated, 1 = omit, 2 = N/A, 3 = min recall, 4 = max recall, 5 = soft recall, 6 = ped recall, 7 = omit ped, 8 = red rest									
	Min Green	3	10	3	10	3	10	3	10	0 - 255 sec
	Passage	1.0	0.0	1.0	0.0	1.0	0.0	1.0	0.0	0.0 - 25.5 sec.
	Yellow	3.0	3.6	3.0	3.6	3.0	3.6	3.0	3.6	0.0 - 25.5 sec. or 3.0 - 25.5
	Red	0.0	1.0	0.0	1.0	0.0	1.0	0.0	1.0	0.0 - 25.5 sec.
	Walk	0	9	0	8	0	10	0	8	0 - 255 sec
	Ped Clearance	0	11	0	13	0	11	0	13	0 - 255 sec

Service Plan 8	Call Mode	0	0	0	0	0	0	0	0	
	0 = actuated, 1 = omit, 2 = N/A, 3 = min recall, 4 = max recall, 5 = soft recall, 6 = ped recall, 7 = omit ped, 8 = red rest									
	Min Green	3	10	3	10	3	10	3	10	0 - 255 sec
	Passage	1.0	0.0	1.0	0.0	1.0	0.0	1.0	0.0	0.0 - 25.5 sec.
	Yellow	3.0	3.6	3.0	3.6	3.0	3.6	3.0	3.6	0.0 - 25.5 sec. or 3.0 - 25.5
	Red	0.0	1.0	0.0	1.0	0.0	1.0	0.0	1.0	0.0 - 25.5 sec.
	Walk	0	9	0	8	0	10	0	8	0 - 255 sec
	Ped Clearance	0	11	0	13	0	11	0	13	0 - 255 sec

Max Plans (Next/2/2/7)

	Phase->	1	2	3	4	5	6	7	8	
MaxPlan 1	Normal Max	14	50	15	34	19	50	15	34	0 - 255 sec
	Fail Max	11	40	12	27	15	40	12	27	
MaxPlan 2	Normal Max	14	50	15	34	19	50	15	34	0 - 255 sec
	Fail Max	11	40	12	27	15	40	12	27	
MaxPlan 3	Normal Max	14	50	15	34	19	50	15	34	0 - 255 sec
	Fail Max	11	40	12	27	15	40	12	27	
MaxPlan 4	Normal Max	14	50	15	34	19	50	15	34	0 - 255 sec
	Fail Max	11	40	12	27	15	40	12	27	
MaxPlan 5	Normal Max	14	50	15	34	19	50	15	34	0 - 255 sec
	Fail Max	11	40	12	27	15	40	12	27	
MaxPlan 6	Normal Max	14	50	15	34	19	50	15	34	0 - 255 sec
	Fail Max	11	40	12	27	15	40	12	27	
MaxPlan 7	Normal Max	14	50	15	34	19	50	15	34	0 - 255 sec
	Fail Max	11	40	12	27	15	40	12	27	
MaxPlan 8	Normal Max	14	50	15	34	19	50	15	34	0 - 255 sec
	Fail Max	11	40	12	27	15	40	12	27	
	Phase->	1	2	3	4	5	6	7	8	0 = use max1 / max2
	Max Mode	1	1	0	1	0	1	0	0	1 = use time of day / coord

CoordinationData		
Coordination Modes (Next/2/3/1)		
Flash Mode	0	0=off, 1=on, 33=time clock, 34=comm, 35=hardwire
Coordination Plan Mode	34	0=free, 1-32 = coord plan 1-32, 33=time clock, 34=comm, 35=hardwire
Offset Seeking Mode	2	0=add only, 1=dwell, 2=fastway
Late Ped	0	0 = off, 1 = on
Coord Walk Rest	1	0 = off, 1 = on, 2 = by TOD circuit 160
Zero Mode(TS2 only)	1	0=start of main street, 1=end of main street, 2=by TOD circuit 144,
(Next/2/3/4/1)		
Coordination Double Cycle	0	0=off, 1=on (no coord ped), 2=on (beginning green coord ped), 3=on
Omit Phase During Repeated	- - - - -	-- = service allowed ; # = service prevented

Coordination Plans (Next/2/3/2)								
Coord Plan	Coordination Phases		Cycle Length	Offset Time	Min Cycle Len Dwell Time	Permissive	Service Plan	Max Plan
	Ring 1	Ring 2						
1	2	6	100	54	0	0	0	0
2	2	6	100	43	0	0	2	0
3	2	6	100	44	0	0	0	0
4	2	6	75	47	0	0	4	0
5	0	0	0	0	0	0	0	0
6	0	0	0	0	0	0	0	0
7	2	6	100	53	0	0	0	0
8	0	0	0	0	0	0	0	0
9	0	0	0	0	0	0	0	0
10	0	0	0	0	0	0	0	0
11	0	0	0	0	0	0	0	0
12	0	0	0	0	0	0	0	0
13	0	0	0	0	0	0	0	0
14	0	0	0	0	0	0	0	0
15	0	0	0	0	0	0	0	0
16	0	0	0	0	0	0	0	0
17	0	0	0	0	0	0	0	0
18	0	0	0	0	0	0	0	0
19	0	0	0	0	0	0	0	0
20	0	0	0	0	0	0	0	0
21	2	6	100	54	0	0	0	0
22	2	6	100	43	0	0	0	0
23	2	6	100	44	0	0	0	0
24	2	6	75	47	0	0	0	0
25	0	0	0	0	0	0	0	0
26	0	0	0	0	0	0	0	0
27	2	6	100	53	0	0	0	0
28	0	0	0	0	0	0	0	0
29	0	0	0	0	0	0	0	0
30	0	0	0	0	0	0	0	0
31	0	0	0	0	0	0	0	0
32	0	0	0	0	0	0	0	0
	0 - 8		0 - 255 sec				0 - 8	

Coordination Plans cont. (Next/2/3/2)

Coord Plan	Use FO for timing	Force Off / Split Times (TS2)								Yield Points / Actuated Times (TS2)	
		1	2	3	4	5	6	7	8	Ring 1	Ring 2
1		16	46	12	26	14	48	12	26	0	0
2		14	48	12	26	18	44	12	26	0	0
3		13	48	12	27	20	41	12	27	0	0
4		13	25	11	26	13	25	11	26	0	0
5		0	0	0	0	0	0	0	0	0	0
6		0	0	0	0	0	0	0	0	0	0
7		9	53	12	26	15	47	12	26	0	0
8		0	0	0	0	0	0	0	0	0	0
9		0	0	0	0	0	0	0	0	0	0
10		0	0	0	0	0	0	0	0	0	0
11		0	0	0	0	0	0	0	0	0	0
12		0	0	0	0	0	0	0	0	0	0
13		0	0	0	0	0	0	0	0	0	0
14		0	0	0	0	0	0	0	0	0	0
15		0	0	0	0	0	0	0	0	0	0
16		0	0	0	0	0	0	0	0	0	0
17		0	0	0	0	0	0	0	0	0	0
18		0	0	0	0	0	0	0	0	0	0
19		0	0	0	0	0	0	0	0	0	0
20		0	0	0	0	0	0	0	0	0	0
21		0	53	0	0	0	53	0	0	0	0
22		0	52	0	0	0	52	0	0	0	0
23		0	54	0	0	0	50	0	0	0	0
24		0	29	0	0	0	29	0	0	0	0
25		0	0	0	0	0	0	0	0	0	0
26		0	0	0	0	0	0	0	0	0	0
27		0	54	0	0	0	54	0	0	0	0
28		0	0	0	0	0	0	0	0	0	0
29		0	0	0	0	0	0	0	0	0	0
30		0	0	0	0	0	0	0	0	0	0
31		0	0	0	0	0	0	0	0	0	0
32		0	0	0	0	0	0	0	0	0	0
0 - 255 sec * = force offs and yield points											

Circuit Mapping (Next/2/3/3)

Circuit Map	Coord Plan	Time Clock Circuit							
		1	2	3	4	5	6	7	8
1	1	97	0	0	0	0	0	0	0
2	2	97	0	0	0	0	0	0	0
3	3	97	0	0	0	0	0	0	0
4	7	97	0	0	0	0	0	0	0
5	1	81	0	0	0	0	0	0	0
6	2	82	0	0	0	0	0	0	0
7	3	83	0	0	0	0	0	0	0
8	4	84	0	0	0	0	0	0	0
9	7	87	0	0	0	0	0	0	0
10	0	0	0	0	0	0	0	0	0
11	0	0	0	0	0	0	0	0	0
12	0	0	0	0	0	0	0	0	0
13	0	0	0	0	0	0	0	0	0
14	0	0	0	0	0	0	0	0	0
15	0	0	0	0	0	0	0	0	0
16	0	0	0	0	0	0	0	0	0
17	0	0	0	0	0	0	0	0	0
18	0	0	0	0	0	0	0	0	0
19	0	0	0	0	0	0	0	0	0
20	0	0	0	0	0	0	0	0	0

coord plan - 0 = free, 1 - 32 = coord plan 1 - 32, 33 = any, 34 none selected

time clock circuits - 0 = not used, or circuits 6 - 185

Dynamic Phase Lengths (Next/2/3/4/4)

Phase ->		1	2	3	4	5	6	7	8	
Back Detector		0	0	0	0	0	0	0	0	0 = none, 1-32 = detector 1-32
Lane Factor		0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0 = none, 1.0 - 5.0
Check Out Detector		0	0	0	0	0	0	0	0	0 = none, 1-32 = detector 1-32
Coord Delta Force Off	Set A	0	0	0	0	0	0	0	0	0 - 255 sec
	Set B	0	0	0	0	0	0	0	0	
	Set C	0	0	0	0	0	0	0	0	
	Set D	0	0	0	0	0	0	0	0	
Free Delta Max	Set A	0	0	0	0	0	0	0	0	
	Set B	0	0	0	0	0	0	0	0	
	Set C	0	0	0	0	0	0	0	0	
	Set D	0	0	0	0	0	0	0	0	

Time of Day Data (Next/2/4/1)

Day Program

	Day Prog	Time	Coord Plan or Circuit	Coord Plan # or Circuit #	Circuit Abbrev	State On/Off
1	1	00:01	Coord Plan	4	CL8	
2	1	11:00	Coord Plan	1	CL1	
3	1	11:00	Circuit	65	SP1	X
4	1	17:00	Coord Plan	4	CL8	
5	1	17:00	Circuit	65	SP1	
6	2	00:01	Coord Plan	4	CL8	
7	2	06:30	Coord Plan	2	CL2	
8	2	06:30	Circuit	13	MX2	
9	2	06:30	Circuit	65	SP1	X
10	2	06:30	Circuit	66	SP2	
11	2	09:00	Coord Plan	1	CL1	
12	2	09:00	Circuit	13	MX2	X
13	2	09:00	Circuit	66	SP2	X
14	2	15:00	Coord Plan	3	CL4	
15	2	15:00	Circuit	13	MX2	
16	2	15:00	Circuit	66	SP2	
17	2	19:00	Coord Plan	7	SFL	
18	2	19:00	Circuit	13	MX2	X
19	2	19:00	Circuit	65	SP1	
20	2	19:00	Circuit	66	SP2	X
21	2	22:00	Coord Plan	4	CL8	
22	0	00:00	Circuit	0	None / Coord Plan	
23	0	00:00	Circuit	0	None / Coord Plan	
24	0	00:00	Circuit	0	None / Coord Plan	
25	0	00:00	Circuit	0	None / Coord Plan	
26	0	00:00	Circuit	0	None / Coord Plan	
27	0	00:00	Circuit	0	None / Coord Plan	
28	0	00:00	Circuit	0	None / Coord Plan	
29	0	00:00	Circuit	0	None / Coord Plan	
30	0	00:00	Circuit	0	None / Coord Plan	
31	0	00:00	Circuit	0	None / Coord Plan	
32	0	00:00	Circuit	0	None / Coord Plan	
33	0	00:00	Circuit	0	None / Coord Plan	
34	0	00:00	Circuit	0	None / Coord Plan	
35	0	00:00	Circuit	0	None / Coord Plan	
36	0	00:00	Circuit	0	None / Coord Plan	
37	0	00:00	Circuit	0	None / Coord Plan	
38	0	00:00	Circuit	0	None / Coord Plan	
39	0	00:00	Circuit	0	None / Coord Plan	
40	0	00:00	Circuit	0	None / Coord Plan	
	1 - 15	hh:mm	X = On = Coord Plan	coord plan 0 - 32 or circuit 1-185		X = On

WEEK PROGRAM (Next/2/4/2)							
	Sun	Mon	Tue	Wed	Thu	Fri	Sat
1	1	2	2	2	2	2	1
2	1	1	1	1	1	1	1
3	1	1	1	1	1	1	1
4	1	1	1	1	1	1	1
5	1	1	1	1	1	1	1
6	1	1	1	1	1	1	1
7	1	1	1	1	1	1	1
8	1	1	1	1	1	1	1
9	1	1	1	1	1	1	1
10	1	1	1	1	1	1	1
0 = none, 1 - 15 = day plan							

0 = none, 1 - 15 = day plan

EXCEPTION DAYS (Next/2/4/6)				
	Week of Month	Month	Day Week/ Month	Day Prog
1	0	0	0	0
2	0	0	0	0
3	0	0	0	0
4	0	0	0	0
5	0	0	0	0
6	0	0	0	0
7	0	0	0	0
8	0	0	0	0
9	0	0	0	0
10	0	0	0	0
11	0	0	0	0
12	0	0	0	0
13	0	0	0	0
14	0	0	0	0
15	0	0	0	0
16	0	0	0	0
17	0	0	0	0
18	0	0	0	0
19	0	0	0	0
20	0	0	0	0
21	0	0	0	0
22	0	0	0	0
23	0	0	0	0
24	0	0	0	0
25	0	0	0	0
26	0	0	0	0
27	0	0	0	0
28	0	0	0	0
29	0	0	0	0
30	0	0	0	0
31	0	0	0	0
32	0	0	0	0
33	0	0	0	0
34	0	0	0	0
35	0	0	0	0
	0 - 5	0 - 12	1 - 7 or 1 - 31	0 - 15

Time Clock References (Next/2/4/5)		
Synch reference Mode	0	0 = timed, 1 = by event
Synch Reference Time	00:00	00:00 - 23:59
Daylight Saving Enable	On	X = On
Reset Time	00:00	00:00 - 23:59

[illegible]

CIRCUIT OVERRIDES 1 - 98 (Next/2/4/4)

1 - Coord Line 1	CL1	2 = TOD	50 - Ped Omit 2	PO2	2 = TOD
2 - Coord Line 2	CL2	2 = TOD	51 - Ped Omit 3	PO3	2 = TOD
3 - Coord Line 4	CL4	2 = TOD	52 - Ped Omit 4	PO4	2 = TOD
4 - Coord Line 8	CL8	2 = TOD	53 - Ped Omit 5	PO5	2 = TOD
5 - Coord Line 16	C16	2 = TOD	54 - Ped Omit 6	PO6	2 = TOD
6 - Coordinated Operation	CRD	2 = TOD	55 - Ped Omit 7	PO7	2 = TOD
7 - Soft Flash	SFL	2 = TOD	56 - Ped Omit 8	PO8	2 = TOD
8 - Enable System Relays	ESR	2 = TOD	57 - Conditonal Service	CVS	2 = TOD
9 - Call to Non Actuated Ring 1	CN1	2 = TOD	58 - Inhibit Simultaneous Gap Out	ISG	2 = TOD
10 -Call to Non Actuated Ring 2	CN2	2 = TOD	59 - Inhibit Hardwire	HWI	2 = TOD
11 - Walk Rest Modifier	WRM	2 = TOD	60 - Ped Override Mode	POM	1 = On
12 - Min Recall	MIN	2 = TOD	61 - Dual Entry	DLE	2 = TOD
13 - Max 2 Both Rings	MX2	2 = TOD	62 - Exclusive Ped	EPD	2 = TOD
14 - Coord Inhibit Max Ring 1	IM1	2 = TOD	63 - Call to Time Clock Mode	CTC	2 = TOD
15 - Coord Inhibit Max Ring 2	IM2	2 = TOD	64 - Dual Enhanced Ped	DEP	2 = TOD
16 - Call to Free	CTF	2 = TOD	65 - Service Plan 1	SP1	2 = TOD
17 - TOD Output 1	TO1	2 = TOD	66 - Service Plan 2	SP2	2 = TOD
18 - TOD Output 2	TO2	2 = TOD	67 - Service Plan 3	SP3	2 = TOD
19 - TOD Output 3	TO3	2 = TOD	68 - Service Plan 4	SP4	2 = TOD
20 - TOD Output 4	TO4	2 = TOD	69 - Service Plan 5	SP5	2 = TOD
21 - TOD Output 5	TO5	2 = TOD	70 - Service Plan 6	SP6	2 = TOD
22 - TOD Output 6	TO6	2 = TOD	71 - Service Plan 7	SP7	2 = TOD
23 - TOD Output 7	TO7	2 = TOD	72 - Service Plan 8	SP8	2 = TOD
24 - TOD Output 8	TO8	2 = TOD	73 - Max Plan 1	MP1	2 = TOD
25 - Vehicle Call Phase 1	VC1	2 = TOD	74 - Max Plan 2	MP2	2 = TOD
26 - Vehicle Call Phase 2	VC2	2 = TOD	75 - Max Plan 3	MP3	2 = TOD
27 - Vehicle Call Phase 3	VC3	2 = TOD	76 - Max Plan 4	MP4	2 = TOD
28 - Vehicle Call Phase 4	VC4	2 = TOD	77 - Max Plan 5	MP5	2 = TOD
29 - Vehicle Call Phase 5	VC5	2 = TOD	78 - Max Plan 6	MP6	2 = TOD
30 - Vehicle Call Phase 6	VC6	2 = TOD	79 - Max Plan 7	MP7	2 = TOD
31 - Vehicle Call Phase 7	VC7	2 = TOD	80 - Max Plan 8	MP8	2 = TOD
32 - Vehicle Call Phase 8	VC8	2 = TOD	81 - Transit Priority Max Group 1	TG1	2 = TOD
33 - Ped Call Phase 1	PC1	2 = TOD	82 - Transit Priority Max Group 2	TG2	2 = TOD
34 - Ped Call Phase 2	PC2	2 = TOD	83 - Transit Priority Max Group 3	TG3	2 = TOD
35 - Ped Call Phase 3	PC3	2 = TOD	84 - Transit Priority Max Group 4	TG4	2 = TOD
36 - Ped Call Phase 4	PC4	2 = TOD	85 - Transit Priority Max Group 5	TG5	2 = TOD
37 - Ped Call Phase 5	PC5	2 = TOD	86 - Transit Priority Max Group 6	TG6	2 = TOD
38 - Ped Call Phase 6	PC6	2 = TOD	87 - Transit Priority Max Group 7	TG7	2 = TOD
39 - Ped Call Phase 7	PC7	2 = TOD	88 - Transit Priority Max Group 8	TG8	2 = TOD
40 - Ped Call Phase 8	PC8	2 = TOD	89 - Inhibit Gap Reducing 1	GR1	2 = TOD
41 - Phase Omit 1	VO1	2 = TOD	90 - Inhibit Gap Reducing 2	GR2	2 = TOD
42 - Phase Omit 2	VO2	2 = TOD	91 - Inhibit Gap Reducing 3	GR3	2 = TOD
43 - Phase Omit 3	VO3	2 = TOD	92 - Inhibit Gap Reducing 4	GR4	2 = TOD
44 - Phase Omit 4	VO4	2 = TOD	93 - Inhibit Gap Reducing 5	GR5	2 = TOD
45 - Phase Omit 5	VO5	2 = TOD	94 - Inhibit Gap Reducing 6	GR6	2 = TOD
46 - Phase Omit 6	VO6	2 = TOD	95 - Inhibit Gap Reducing 7	GR7	2 = TOD
47 - Phase Omit 7	VO7	2 = TOD	96 - Inhibit Gap Reducing 8	GR8	2 = TOD
48 - Phase Omit 8	VO8	2 = TOD	97 - Lag 1	LG1	2 = TOD
49 - Ped Omit 1	PO1	2 = TOD	98 - Lag 3	LG3	2 = TOD

PREEMPTION SEQUENCE 1 - 4 (Next/2/5)

Seq	Interval	Instruction	Phases Serviced	Interval Time	Hold On Input	Output On	Output Mode	Instructions -
1	1	0	- 2 - - 5 - - -	10	On	- - - - - 0	0	0 = service phases
	2	99	- 2 - - - 6 - -	0	Off	- - - - - 0	0	1 - 9 = special intervals 1 - 9
	3	0	- - - - - - - -	0	Off	- - - - - 0	0	10 = service phase, allow FYA
	4	0	- - - - - - - -	0	Off	- - - - - 0	0	15 = serve PE if PE phase is green
	5	0	- - - - - - - -	0	Off	- - - - - 0	0	90 = go to all red
	6	0	- - - - - - - -	0	Off	- - - - - 0	0	91 = soft flash on
	7	0	- - - - - - - -	0	Off	- - - - - 0	0	92 = soft flash off
	8	0	- - - - - - - -	0	Off	- - - - - 0	0	93 = enable peds and phases
	9	0	- - - - - - - -	0	Off	- - - - - 0	0	94 = disable peds
	10	0	- - - - - - - -	0	Off	- - - - - 0	0	95 = priority return
2	1	0	- - - 4 - - 7 -	10	On	- - - - - 0	0	96 = enable coord with ped
	2	99	- - - 4 - - - 8	0	Off	- - - - - 0	0	97 = enable coord without ped
	3	0	- - - - - - - -	0	Off	- - - - - 0	0	98 = return with no calls
	4	0	- - - - - - - -	0	Off	- - - - - 0	0	99 = return with vehicle calls
	5	0	- - - - - - - -	0	Off	- - - - - 0	0	100 = jump to step in interval time
	6	0	- - - - - - - -	0	Off	- - - - - 0	0	101 = use interval time as resetable gap timer
	7	0	- - - - - - - -	0	Off	- - - - - 0	0	Instructions cont.-
	8	0	- - - - - - - -	0	Off	- - - - - 0	0	200 = light rail train phase with out peds
	9	0	- - - - - - - -	0	Off	- - - - - 0	0	201 = light rail train phase with peds
	10	0	- - - - - - - -	0	Off	- - - - - 0	0	202 = return to highest queue / delay phase (this uses the dynamic phase length back detectors)
3	1	0	1 - - - - 6 - -	10	On	- - - - - 0	0	Phases Serviced - phases 1 - 8
	2	99	- 2 - - - 6 - -	0	Off	- - - - - 0	0	Interval Time - 0 - 255 sec or interval 1 - 10
	3	0	- - - - - - - -	0	Off	- - - - - 0	0	Hold on Input - X = on
	4	0	- - - - - - - -	0	Off	- - - - - 0	0	Outputs On - output 1 - 8
	5	0	- - - - - - - -	0	Off	- - - - - 0	0	Output Modes -
	6	0	- - - - - - - -	0	Off	- - - - - 0	0	0 = all steady on
	7	0	- - - - - - - -	0	Off	- - - - - 0	0	1 = all flash together
	8	0	- - - - - - - -	0	Off	- - - - - 0	0	2 = odd flashes WIG, even flashes WAG
	9	0	- - - - - - - -	0	Off	- - - - - 0	0	3 = 1 - 4 steady on, 5 - 8 all flash together
	10	0	- - - - - - - -	0	Off	- - - - - 0	0	
4	1	0	- - 3 - - - - 8	10	On	- - - - - 0	0	
	2	99	- - - 4 - - - 8	0	Off	- - - - - 0	0	
	3	0	- - - - - - - -	0	Off	- - - - - 0	0	
	4	0	- - - - - - - -	0	Off	- - - - - 0	0	
	5	0	- - - - - - - -	0	Off	- - - - - 0	0	
	6	0	- - - - - - - -	0	Off	- - - - - 0	0	
	7	0	- - - - - - - -	0	Off	- - - - - 0	0	
	8	0	- - - - - - - -	0	Off	- - - - - 0	0	
	9	0	- - - - - - - -	0	Off	- - - - - 0	0	
	10	0	- - - - - - - -	0	Off	- - - - - 0	0	

SEQUENCE TIMING (Next/2/5/0)												
Sequence		1	2	3	4	5	6	7	8			
Input Memory										X = on		
Input Priority		6	6	6	6	0	0	0	0	0 = lowest, - 8 = highest		
Entry (Transition) Parameters	Min Green	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0 - 25.5 sec 0.0 would time the normal function time		
	Walk	4.0	4.0	4.0	4.0	0.0	0.0	0.0	0.0			
	Ped Clear	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0			
	Overlap Yellow	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0 - 25.5 sec		
	Overlap Red	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0			
	Delay to Preempt	0	0	0	0	0	0	0	0	0 - 255 sec		
	Delay Ped Omit	0	0	0	0	0	0	0	0			
	Delay Phase Omit	0	0	0	0	0	0	0	0			
Min Reservice		0	0	0	0	0	0	0	0	0 - 255 min		
Overlap Inhibits		- - - -	- - - -	- - - -	- - - -	- - - -	- - - -	- - - -	- - - -			
Entry (Transition) Parameters	Exit to Coord Plan Offset by X	0	0	0	0	0	0	0	0	0 - 20		
	Exit Coord Plan Time	0	0	0	0	0	0	0	0	0 - 60 min		
	Exit to Max Plan	0	0	0	0	0	0	0	0	0 - 8		
	Exit Free Time	0	0	0	0	0	0	0	0	0 - 60 min		
	Override Time	0	0	0	0	0	0	0	0			
	Fail Time	0	0	0	0	0	0	0	0			
	Exit Mode Time	0	0	0	0	0	0	0	0			

PRIORITY RETURN AND SPECIAL INTERVALS (Next/2/5/0/6, Next/2/5/9)														
Phase / Overlap		1	2	3	4	5	6	7	8	A	B	C	D	
Priority Return	Enable	Off												
	A (max)	0	0	0	0	0	0	0	0	0 - 100% of currently used max				
	B (max)	0	0	0	0	0	0	0	0					
	C (max)	0	0	0	0	0	0	0	0					
	D (max)	0	0	0	0	0	0	0	0					
	E (max)	0	0	0	0	0	0	0	0					
	Ped Clear	0	0	0	0	0	0	0	0	0 - 100% of currently used ped clearance				
Queue Delay Recovery		0	0	0	0	0	0	0	0	0 - 255 sec				
Special Intervals	1	0	0	0	0	0	0	0	0	0	0	0	0	0 = Dark 1 = green don't walk 2 = green walk 3 = green flashing don't walk 4 = yellow 5 = red 6 = flashing yellow WIG 7 = flashing yellow WAG 8 = flashing red WIG 9 = flashing red WAG 10 = walk only 11=flashing don't walk only
	2	0	0	0	0	0	0	0	0	0	0	0	0	
	3	0	0	0	0	0	0	0	0	0	0	0	0	
	4	0	0	0	0	0	0	0	0	0	0	0	0	
	5	0	0	0	0	0	0	0	0	0	0	0	0	
	6	0	0	0	0	0	0	0	0	0	0	0	0	
	7	0	0	0	0	0	0	0	0	0	0	0	0	
	8	0	0	0	0	0	0	0	0	0	0	0	0	
	9	0	0	0	0	0	0	0	0	0	0	0	0	

LIGHT RAIL TRAIN (Next/2/5/0/7)							
Light Rail Train		1	2	3	4		
Associated Preempt		0	0	0	0	0 = none, preempt 1 - 8	
Time to Green		0	0	0	0	0 - 255 sec	
Horizontal Bar Flash Time		0.0	0.0	0.0	0.0		
Vertical Bar Flash Time		0.0	0.0	0.0	0.0	0.0 - 25.5 sec	
Min Duration		0	0	0	0	0 - 255 sec	

COMMUNICATION DATA (Next/2/6)					
1st Central Phone Number		2nd Central Phone Number			
Modem Setup String					
Intersection Name					
Central Port		6 = UDP/AB3418/C14S			
System Mode		0			
System Port		0			
System ID	22	Local ID	19	IP Address	192.169.21.13
				Gateway Address
Serial Port Parameters		Baud Rates	Flow Control		
Port1 (Slot A2 Upper)		0 = 1200	On		
Port2 (Slot A2 Lower)		0 = 1200	On		
Port3 (Slot A1 Upper)		0 = 1200	Off		
Port4 (Slot A1 :power pr C50S)		2 = 9600			
0 = 1200, 1 = 2400, 2 = 9600, 3 = 19200 baud					

COMMUNICATION REPORTS (Next/2/6/6, Next/2/6/7)			
Volume Log Period		15	
MOE Log Period		15	
0 = disabled, 1,2,3,4,5,6,10,12,15,20,30,60 minutes			
Alarm 1	0 = none	Soft Flash	0 = none
Alarm 2	0 = none	Manual Control Enable (MCE)	0 = none
Alarm 3	0 = none	Emergency or Railroad Preempt	1 = schedule A
Alarm 4	0 = none	Not Used	
Alarm 5	0 = none	Cycle Failure	0 = none
Not Used		Coordination Failure	0 = none
Not Used		Keyboard use /Data Changed	0 = none
Not Used		Coord Running / Free	0 = none
Power On / Off	0 = none	Cabinet Door	0 = none
Checksum Failure	0 = none	Not Used	
Video / Detector Failure	0 = none	Monitor Status	0 = none
Not Used			
0 = none; 1 = schedule A; 2 = schedule B 3 = schedule C; 4 = schedule R			

TRANSIT PRIORITY (Next/2/7)									
	1	2	3	4	5	6	7	8	
Phases	2	NONE	6	NONE	NONE	NONE	NONE	NONE	Phases 1 - 8 (max of 2 compatible phases)
PE Enable (6.25Hz TP call on PE)	X	X	X	X	X	X	X	X	X = 6.25 Hz signal will activate TP
Priority	0	1	0	0	0	1	0	0	0 - 8, 8 = highest
Memory									X = on
Delay Time	0	0	0	0	0	0	0	0	0 - 255 sec
Minimum Reserve Time (per input)	5	0	5	0	0	5	0	0	0 - 255 min
Override Time	0	0	0	0	0	0	0	0	0 - 255 sec
Bus Extend	0	0	0	0	0	0	0	0	0 - 255 min
Minimum Reserve Time (all inputs)	0	0 - 255 min							
Free Operation Mode	0	0 = use shortest of max 1 or 2, 1 - 8 = use max time of group 1 - 8, 9 = use time of day circuit							

TRANSIT PRIORITY ALTERNATE FORCE OFF PLANS (Next/2/7/6)									
Current Coord Plan	1	2	3	4	5	6	7	8	0 = none 17 - 32 = coord plan 17 - 32
Alternate TP Force Off Plan	21	22	23	24	0	0	27	0	
Current Coord Plan	9	10	11	12	13	14	15	16	
Alternate TP Force Off Plan	0	0	0	0	0	0	0	0	

GROUP TIMING (Next/2/7/5)									
	Phase -->	1	2	3	4	5	6	7	8
Group 1	Max Times	10	0	8	25	10	0	8	25
	Walk Times	0	0	0	8	0	0	0	8
Group 2	Max Times	0	0	7	25	10	0	8	25
	Walk Times	0	0	0	8	0	0	0	8
Group 3	Max Times	0	0	7	18	10	0	0	18
	Walk Times	0	0	0	8	0	0	0	8
Group 4	Max Times	0	0	7	18	5	0	0	16
	Walk Times	0	0	0	8	0	0	0	8
Group 5	Max Times	0	0	0	0	0	0	0	0
	Walk Times	0	0	0	0	0	0	0	0
Group 6	Max Times	0	0	0	0	0	0	0	0
	Walk Times	0	0	0	0	0	0	0	0
Group 7	Max Times	0	0	7	16	10	0	0	16
	Walk Times	0	0	0	8	0	0	0	8
Group 8	Max Times	0	0	0	0	0	0	0	0
	Walk Times	0	0	0	0	0	0	0	0

TRUCK PRIORITY (Next/2/7/9)					
Truck Priority -->	1	2	3	4	
Associated Transit Priority	0	0	0	0	0 = none 1 - 8 = transit priority 1 - 8
Leading Detector	0	0	0	0	0 = none, 1 - 32 = detector 1 - 32
Trailing Detector	0	0	0	0	
Stop Bar Distance	0	0	0	0	0 - 999 feet
ATrap Distance	0 . 0	0 . 0	0 . 0	0 . 0	0.0 - 25.5 feet
Minimum Speed	0	0	0	0	0 - 100 mph
Minimum Length	0	0	0	0	0 - 255 feet
Downhill Grade (%)	0	0	0	0	0 - 20%
Uphill Grade (%)	0	0	0	0	
Undersized Vehicle					X = Enabled

170 INPUTS (Next/2/8/1)

C1-39	101 - Veh Detector 9	C1-67	22 - Ped Detector 2
C1-40	113 - Veh Detector 19	C1-68	26 - Ped Detector 6
C1-41	106 - Veh Detector 14	C1-69	24 - Ped Detector 4
C1-42	118 - Veh Detector 24	C1-70	28 - Ped Detector 8
C1-43	102 - Veh Detector 10	C1-71	151 - Preempt In 1
C1-44	114 - Veh Detector 20	C1-72	152 - Preempt In 2
C1-45	107 - Veh Detector 15	C1-73	153 - Preempt In 3
C1-46	161 - Veh Detector 25	C1-74	154 - Preempt In 4
C1-47	105 - Veh Detector 13	C1-75	254 - Pin Not Used
C1-48	117 - Veh Detector 23	C1-76	104 - Veh Detector 12
C1-49	112 - Veh Detector 18	C1-77	116 - Veh Detector 22
C1-50	164 - Veh Detector 28	C1-78	111 - Veh Detector 17
C1-51	199 - LRT Ped Inhibit	C1-79	163 - Veh Detector 27
C1-52	155 - Preempt In 5	C1-80	82 - Interval Advance
C1-53	85 - Manual Control Enable	C1-81	137 - Conflict Monitor Status/Flash
C1-54	254 - Pin Not Used	C1-82	62 - Stop Timing Ring 1
C1-55	15 - Veh Detector 5	C11-15	254 - Pin Not Used
C1-56	11 - Veh Detector 1	C11-16	254 - Pin Not Used
C1-57	17 - Veh Detector 7	C11-17	254 - Pin Not Used
C1-58	13 - Veh Detector 3	C11-18	254 - Pin Not Used
C1-59	16 - Veh Detector 6	C11-19	254 - Pin Not Used
C1-60	12 - Veh Detector 2	C11-20	254 - Pin Not Used
C1-61	18 - Veh Detector 8	C11-21	254 - Pin Not Used
C1-62	14 - Veh Detector 4	C11-22	254 - Pin Not Used
C11-10	254 - Pin Not Used	C11-23	254 - Pin Not Used
C11-11	254 - Pin Not Used	C11-24	254 - Pin Not Used
C11-12	254 - Pin Not Used	C11-25	254 - Pin Not Used
C11-13	254 - Pin Not Used	C11-26	254 - Pin Not Used
C1-63	103 - Veh Detector 11	C11-27	254 - Pin Not Used
C1-64	115 - Veh Detector 21	C11-28	254 - Pin Not Used
C1-65	108 - Veh Detector 16	C11-29	254 - Pin Not Used
C1-66	162 - Veh Detector 26	C11-30	254 - Pin Not Used

INPUTS AND OUTPUTS OPTIONS (Next/2/8/3)

Connector Type	C1/C11	Change I/O	1 = Enabled
0 = C1/C11; 1 = MS-A/B/C/D; 2 = TS2 Port X = On (After a download without a power on - off cycle)			

170 OUTPUTS (Next/2/8/2)

C1-2	44 - Don't Walk, Ph 4	C1-35	131 - TOD Output 1
C1-3	64 - Walk, Ph 4	C1-36	132 - TOD Output 2
C1-4	14 - Red, Ph 4	C1-37	133 - TOD Output 3
C1-5	24 - Yellow, Ph 4	C1-38	134 - TOD Output 4
C1-6	34 - Green, Ph 4	C1-100	53 - Ped Clear, Ph 3
C1-7	13 - Red, Ph 3	C1-101	51 - Ped Clear, Ph 1
C1-8	23 - Yellow, Ph 3	C1-102	187 - Soft Flash
C1-9	33 - Green, Ph 3	C1-103	147 - Watchdog
C1-10	42 - Don't Walk, Ph 2	C1-83	43 - Don't Walk, Ph 3
C1-11	62 - Walk, Ph 2	C1-84	63 - Walk, Ph 3
C1-12	12 - Red, Ph 2	C1-85	116 - Overlap D, Red
C1-13	22 - Yellow, Ph 2	C1-86	115 - Overlap D, Yellow
C1-15	32 - Green, Ph 2	C1-87	114 - Overlap D, Green
C1-16	11 - Red, Ph 1	C1-88	113 - Overlap C, Red
C1-17	21 - Yellow, Ph 1	C1-89	112 - Overlap C, Yellow
C1-18	31 - Green, Ph 1	C1-90	111 - Overlap C, Green
C1-19	48 - Don't Walk, Ph 8	C1-91	41 - Don't Walk, Ph 1
C1-20	68 - Walk, Ph 8	C1-93	61 - Walk, Ph 1
C1-21	18 - Red, Ph 8	C1-94	106 - Overlap B, Red
C1-22	28 - Yellow, Ph 8	C1-95	105 - Overlap B, Yellow
C1-23	38 - Green, Ph 8	C1-96	104 - Overlap B, Green
C1-24	17 - Red, Ph 7	C1-97	103 - Overlap A, Red
C1-25	27 - Yellow, Ph 7	C1-98	102 - Overlap A, Yellow
C1-26	37 - Green, Ph 7	C1-99	101 - Overlap A, Green
C1-27	46 - Don't Walk, Ph 6	C11-1	254 - Pin Not Used
C1-28	66 - Walk, Ph 6	C11-2	254 - Pin Not Used
C1-29	16 - Red, Ph 6	C11-3	254 - Pin Not Used
C1-30	26 - Yellow, Ph 6	C11-4	254 - Pin Not Used
C1-31	36 - Green, Ph 6	C11-5	254 - Pin Not Used
C1-32	15 - Red, Ph 5	C11-6	254 - Pin Not Used
C1-33	25 - Yellow, Ph 5	C11-7	254 - Pin Not Used
C1-34	35 - Green, Ph 5	C11-8	254 - Pin Not Used

CONTROLLER ID

Manufacturer ID	NORTHWEST SIGNAL
Model ID	Voyage-0 v04.01.00
Protocol Revision ID	AB3418E V1

